



Construction

Type	Urban Loft		
Widths	7 1/2" (189 mm)		
Length - Multi-Lengths	Majority 74" (majority 1880 mm)		
Edges	Micro-V on all 4 sides		
Joint	Tongue and groove		
Thickness	Total	0.60" (15.2 mm)	
	Wear Layer	0.14" (3.5 mm) dry solid sawn	
	Core:	3/8" (9.7 mm) cross grain SPF	
	Balancing base layer:	0.08" (2 mm) Poplar Veneer	
Relative Humidity	35% - 65%		
Fabrication	Imported product designed in Canada (Quebec)		

Products

Series	Urban Loft		
Species	White Oak		
Grade	Urban Loft		
Grade Description	Please refer to the Species and Grade Guides available in the "Useful Literature" section of the website.		
Styles	Character		
Texture	Wire Brushed		
Sheens (Gloss Levels)	Matte (10%)		
Colors	Brooklyn, Chelsea Cream, Cité, Fifth Avenue, Exposed Oak, Greystone, Old York, Station 54		

Finish

Titanium™ Finish	Polymerized titanium finish enhanced with nanotechnology			
Characteristics	Appearance:	Superior	Durability:	Superior
	Gloss losing resistance:	Superior	Stain Resistance:	Superior
	Easy to maintain:	Superior	Easy to repair:	Superior
	Solvent & Water:	Free	Formaldehyde:	Free
	Static Friction Coefficient ASTM D-2394-99	Slippery resistance coefficient more than 0.5		

Installation, Usage, Warranties & Accessories

Installation	Levels:	Basement, main and upper floors	Methods:	Nailed, stapled, glued or floated
	Subfloors:	Ceramic, vinyl, concrete, plywood or OSB 3/4"		
Radiant Heat	Compatible			
Maintenance	Recommended hardwood flooring cleaning products			
Uses	Residential & light commercial			
Warranties <i>(Please refer to the Installation Guide)</i>	Structural:	Lifetime		
	Finish wear-through:	Residential: 35 years	Light Commercial: 5 years	
Available Moldings	Square Stair Nosing:	84" L x 4 1/8" W x 0.59" H (2,133 mm L x 105 mm W x 15 mm H)	Quarter Round:	84" L x 3/4" W x 3/4" H (2,133 mm L x 19 mm W x 19 mm H)
	T-Molding:	84" L x 2" W x 3/4" H (2,133 mm L x 50.8 mm W x 19 mm H)		
	Threshold:	84" L x 2 1/8" W x 3/4" H (2,133 mm L x 53.98 mm W x 19 mm H)		
	<i>Please refer to our Molding Guide for more information.</i>			

Product standards

Formaldehyde Emission ASTM D6007-14	Below limit of quantitation of 0.008 ppm
VOC Total ASTM-D-6670-01	0.003 ppm (depends on wood species)
Surface Burning ASTM-E84	Classe 3 or C
R Value	R 0.44 to 0.51 (depends on wood species)
Critical Radiant Flux ASTM-E-648-94a	0.25 - 0.40 watt/cm ² (depends on wood species)

Certifications

CARB 93120 Phase II	Compliant
Lacey Act	Compliant

Packaging

Coverage per box	22.7 ft ² (2.11 m ²)
Box size	74 13/32" L x 7 9/16" W x 3 25/32" H (1,890 mm L x 192 mm W x 96 mm H)
Box weight	35 lbs
Boxes per pallet	35
Coverage per pallet	794.5 ft ² (73.81 m ²)
Pallet size	75 33/6" L x 28 3/4" W x 37 51/64" H (1,918.1 mm L x 730.25 mm W x 960 mm H)

Relative Species Hardness

NWFA Janka	White Oak: 1,360 lbs - 5% harder
Hardness Test (ASTM-D-143)	
Red Oak 1290 lbs* - 100% *lbs = Applied force in pounds	